

Potential impact of severe weather on hydraulic performance of a field-scale wastewater treatment plant: A case study of baffle-based pond

Saifhon Tomkratoke, Teppatat Pantuphag (Speaker), Sirod Sirisup

Data-driven Simulation and Systems Research Team
National Electronics and Computer Technology Center, Thailand.

1

Presentation Structure

- introduction
- Objective
- Methodology
- Result
- Conclusion

2

Introduction

- Wastewater treatment schemes are essential due to current water pollution situation in Thailand.
- Waste Stabilization Pond with baffles (WSPB) can be one of the possible strategies.
- WSPB is potentially disturbed by the external factors such as a heavy rainfalls, stormwater, causing the overflow into the waste water treatment plant.

3


Objective

- To Understand the hydraulic behaviors in operating condition and an extreme event.
- To Investigate the development scheme of WSPB and applying to design schemes of wastewater treatment management.

4


Methodology

- **Operating condition**
 - Select number of baffle
- **Stormwater condition**
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
 - Improvement scheme
 - Porous media + 2 elevated Baffles



Methodology

- **Operating condition**
 - Select number of baffle
- **Stormwater condition**
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
 - Improvement scheme
 - Porous media + 2 elevated Baffles





2.5 m²

1.5 m²

Methodology

- **Operating condition**
 - Select number of baffle
- **Stormwater condition**
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
 - Improvement scheme
 - Porous media + 2 elevated Baffles




Mixing sizes of Obstacles

7

Methodology


- **Operating condition**
 - Select number of baffle
- **Stormwater condition**
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
 - Improvement scheme
 - Porous media + 2 elevated Baffles



8


Methodology

- Operating condition
 - Select number of baffle
- **Stormwater condition**
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
- Improvement scheme
 - Porous media + 2 elevated Baffles




Methodology

- **Computational Detail**
 - A synthetic flow rate is setup to be upstream condition.
 - The outlet is prescribed with the free surface (Water level)
 - Open software "SCHISM" (Ref. www.schism.wiki)



Result


Operating condition: Select number of baffle



11

Result


Stormwater condition: effect of spillway



12

Result


Stormwater condition: effect of Porous media filter



13

Result

Stormwater condition: Flooding situation




14


Result

Stormwater condition: Improvement scheme


Inlet 1 (2.5 sqm)




Modified case : inlet 1



Inlet 2 (1.5 sqm)



Modified case : inlet 2



15

Conclusion

- The number of baffles and inlet size influence eddy cell's development in WSP.
- The best result is 8 baffles with the inlet(spillway) size of 2.5 square meters.
- Porous-media-like filter structures could improve overall performance.
- Numerical simulation helps improve design scheme of wastewater treatment plants/infrastructures.




16

THANK YOU

17

Result


Extreme event: Modified model



18

Result


Operating condition



19

Result

Operating condition




20

Methodology

Computational Detail


- A synthetic flowrate is setup to be upstream condition.
- The outlet is prescribed with the free surface (Water level)
- Open software "SCHISM" (Ref. www.schism.wiki)



21

Methodology

- Design Waste Stabilization ponds by testing effect of baffle and observing hydraulic efficiency.
 - Pond's size: $L1/L2 = 1/2.6 = 5/13$
 - Number of baffle: 0 2 and 8
- Study a porous media behavior by Mixing Obstacles which the diameters 0.15 and 0.5 meters
- Study effect of stormwater by setting the synthetic flow to be inlet




22

Methodology

Design Geometry


- Create a initial pond
- Select number of baffles (2 8)
- Study effect of spillway
- Study effect of stormwater
- Improvement scheme
 - Elevated Baffles



23

Methodology

- Operating condition
 - Select number of baffle
- Stormwater condition
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
 - Improvement scheme




24

Methodology

Forcing an extreme event

- Create initial pond
- Select number of baffles (2 8)
- Study effect of spillway
- **Stormwater Characteristic**
- Improved WSP
 - Filter
 - Elevated Baffles




25

Methodology

Forcing data


- Create initial pond
- Select number of baffles (2 8)
- Study effect of spillway
- **Stormwater Characteristic**
- Improved WSP
 - Filter
 - Elevated Baffles



26

Result


Extreme event



27

Result

Extreme event



28

Methodology

- Operating condition
 - Select number of baffle
- Stormwater condition
 - Study effect of spillway
 - Study effect of filter
 - Flooding situation
 - Improvement scheme

